

# Adjustable Pressure Drop Activated Trap Primer

Product Specifications



## FEATURES

- Adjusting Screw allows for adjustments to be made to the static line pressure
- Primer is to be connected to cold, fresh water supply lines of 1 1/2" diameter or less
- Operating Range: 20 psi minimum to 80 psi (138 to 552 kpa) max
- Pressure requirement: 10 psi (70 kpa) pressure drop across the valve to activate
- Material: 360 brass, EPDM E70 O-rings, Dow #7 Silicone, #60 stainless steel mesh screen, stainless steel adjustment screw



Floor Drain Trap Primer Distribution Chart			
✓ To Submit	Part #	# of Drains	Distribution Units
	MLP2-500	1	N/A
	MLP2-500	2	MLDU-U
	MLP1-500	3	MLDU-U
	MLP1-500	4	MLDU-U

*MLP1-500 will prime 1-4 floor drains using our patented MLDU-U Distribution unit (sold separately). MLP2-500 will prime 1-2 floor drains using our patented MLDU-U Distribution unit (sold separately).*

## Warranty

See warranty information for more details.

All dimensions listed are nominal. MAINLINE® reserves the right to make product and material changes at any time without notice.



Contact your sales representative for more information or visit our website at [mainlinecollection.com](http://mainlinecollection.com)