



MAINLINE®

Reliably Comfortable.® 

MLT955WH

Wireless Universal

Up to 2 Heat 2 Cool Conventional
Up to 3 Heat 2 Cool Heat Pump
Battery or Hardwire
7D, 5/1/1, Non-Programmable



MLT955WH

Reliably Comfortable.®



Universal Subbase

All Mainline thermostats have the same size footprint, making model upgrading a breeze. No wiring and no painting necessary.



Private Label Badge

All Mainline thermostats share a removable badge system that can be easily replaced with a custom badge that has your company's contact information. This free service is a great way to generate future business for your company.



Exclusively For Professionals

You don't have to compete with the giant big-box retailers. We sell our products exclusively to professional HVAC distributors.

MLT955WH Specifications

Model #	C Commercial 2/4 Time Periods (Occupied/Unoccupied)	Stages of heat	Stages of cool	Heat pump with Auxiliary	Compatible with Conventional systems	Display size (square inches)	Outdoor temperature sensor compatible	Auto change-over	Filter change reminder	Room temperature calibration	Adjustable temperature swing	Programmable fan	Adjustable setpoint fan	Humidity limits	Memory type (permanent)	Touchscreen	Warranty (Years)	Remote capable sensor	Terminals	
	7D 7 Day Programmable																			5 1/1 5/1/1 Programmable
MLT955WH	7D	5/1/1	NP	C	3*	2	•	•	13	•	•	•	•	•	•	•	•	5	•	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B, H, D

* 2 heat stages for conventional heat

Specifications

The display range of temperature	41°F to 95°F (5°C to 35°C)
The control range of temperature.....	44°F to 90°F (7°C to 32°C)
Load Rating.....	1 amp per terminal, 1.5 amp maximum all terminals combined
Swing (cycle rate differential).....	Heating is adjustable from 0.2° to 2.0° Cooling is adjustable from 0.2° to 2.0°
Power source	18 to 30 VAC, NEC Class II, 50/60 Hz for hardwire Battery power from 2 AA Alkaline batteries
Operating ambient	32°F to +105°F (0°C to +41°C)
Operating humidity	90% non-condensing maximum
Dimensions of thermostat	4.7" W x 4.3" H x 0.9" D



Rev. 1919